

Parapet

A wall bounds or subdivides spaces. Walls are usually vertical, or near vertical, planar elements, often designed to bear structural loads. It can also simply be an architectural element which is non-load bearing.

A parapet is wall-like barrier to protect human occupants from falling, or to prevent the spread of fires. Often designed at the edge of balconies, terraces or roofs.

IFC 2x3 note

For IFC2x3 use the PredefinedType enumerator of STANDARD.

IfcElementType	IfcWall	=IfcExportAs
IfcPredefinedType	PARAPET	=IfcExportType
Suggested Filename:	Wall_Parapet	
Suggested LOD (Design Model)	300	
Suggested Primary Discipline	Structural; Architectural	

Source

Property Categories

Classification

BIM Forum	Admin data	Masterformat	03 40 00 : Precast Concrete
IFC 2x3	Code compliance data		04 20 00 : Unit Masonry
IFC4 Add2	Construction logistics data		05 41 00 : Structural Metal Stud Framing
NATSPEC BIM	Cost data		06 11 00 : Wood Framing
NATSPEC Spec	Facilities management data		03 30 00 : Cast-in-Place Concrete
	Geometric data	NatspecWorksection	0310 Concrete – combined
	Manufacturer data		0321 Precast concrete
	Performance data		0322 Tilt-up concrete
	Scheduling data		0331 Brick and block construction
	Spatial and location data	Omniclass Table 21 Elements	21-02 20 10 20 : Exterior Wall Construction
	Specification data	Omniclass Table 22 Work	22-03 30 00 : Cast-in-Place Concrete
	Sustainability data	Results	22-03 40 00 : Precast Concrete

	22-04 20 00 : Unit Masonry
	22-05 41 00 : Structural Metal Stud Framing
	22-06 11 00 : Wood Framing
Omniclass Table 23 Products	23-13 35 21 : Structural Walls
Uniclass Elements	EF_25_55 : Barriers
Uniclass Products	Pr_20_65_60_48 : Light gauge steel frame walls
	Pr_20_65_78_88 : Timber framed and panelled shelters
	Pr_20_93_51 : Masonry flooring units
	Pr_20_93_85 : Structural walling units
Uniclass Systems	Ss_25_10 : Framed wall systems
	Ss_25_11 : Monolithic wall structure systems
	Ss_25_12 : Panel wall structure systems
	Ss_25_13 : Unit wall structure systems
	Ss_25_15_60_60 : Pedestrian parapet systems
Unifomat	B2010.20 : Exterior Wall Construction

Property	Source	Description
Admin data		
CreatedBy	NATSPEC BIM	The name of the person, organisation or library provider that created the object.
CreatedByURL	NATSPEC BIM	URL hyperlink to the object creator's website.
ModifiedIssue	NATSPEC BIM	To record the last date of issue (version or revision) of the object within an object library. Add the date in the following format <yyyymmdd.no> where the 'no' suffix is equal to the number of times the object has been issued on that date. For example 20180316.01.
Reference	PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Reference ID for a specified type in a project (e.g. type 'A-1'). Also known as Construction type. Provide as an alternative to the name of the object type, if software does not support object types.
Code compliance data		
FireRating	BIM Forum NATSPEC BIM PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Fire rating of object. Also known as the FRL (Fire Resistance Level) e.g. 60/60/60.
SurfaceSpreadOfFlame	PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Indication of how flames spread around surface, according to the applicable building code.
Construction logistics data		
Construction	BIM Forum	
ConstructionMethod	NATSPEC BIM	
GrossWeight	Qto_WallBaseQuantities (IFC4) NATSPEC BIM	
NetWeight	Qto_WallBaseQuantities (IFC4)	Takes all openings or recesses into account.

ShippingWeight	NATSPEC BIM	
Status	PSet_WallCommon (IFC4)	Status of the object, predominately used in renovation or retrofitting projects. Complete value with: NEW, EXISTING, DEMOLISH, TEMPORARY, OTHER, NOTKNOWN or UNSET
StoragePlacementOnSite	NATSPEC BIM	
Cost data		
AdditionalTax	NATSPEC BIM	
AssemblyCost	NATSPEC BIM	
AssetAccountingType	Pset_Asset (IFC4)Pset_Asset (IFC2x3)	Asset type for accounting purposes. Complete value with: FIXED, NONFIXED, OTHER, NOTKNOWN or UNSET (PEnum_AssetAccountingType)
AssetInsuranceType	Pset_Asset (IFC4)Pset_Asset (IFC2x3)	Type of insurance rating. Complete value with: PERSONAL, REAL, OTHER, NOTKNOWN or UNSET (PEnum_AssetInsuranceType)
AssetTaxType	Pset_Asset (IFC4)Pset_Asset (IFC2x3)	Type of taxation group. Complete value with: CAPITALISED, EXPENDED, OTHER, NOTKNOWN or UNSET (PEnum_AssetTaxType)
ConceptualCost	NATSPEC BIM	
CostOverRun	NATSPEC BIM	
FutureCostAssumptions	NATSPEC BIM	
InstallationCost	NATSPEC BIM	
InstalledCost	NATSPEC BIM	
PurchaseInformation	NATSPEC BIM	
RecordedActualCost	NATSPEC BIM	

ShippingCost	NATSPEC BIM	
TotalOwnershipCost	NATSPEC BIM	
Facilities management data		
AcquisitionDate	Pset_ManufacturerOccurrence (IFC4) Pset_ManufacturerOccurrence (IFC2x3)	Date the item was purchased (Format: YYYY-MM-DD).
AssessmentCondition	NATSPEC BIM Pset_Condition (IFC4)	Overall condition rating based on assessment. Rating scale to be agreed prior (e.g. Good, OK , Poor).
AssessmentDate	Pset_Condition (IFC4)	Date of overall condition assessment (Format: YYYY-MM-DD).
AssessmentDescription	Pset_Condition (IFC4)	Qualitative description of the condition.
ComponentID	NATSPEC BIM	
Exclusions	Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	Items, conditions or actions that may be excluded from the warranty or that may cause the warranty to become void.
ExpectedLife	NATSPEC BIM	Expected serviceable life of object.
InstallationDate	NATSPEC BIM	Format: YYYY-MM-DD.
IsExtendedWarranty	Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	Complete value with: TRUE or FALSE (IfcBoolean)
ReplacementCost	NATSPEC BIM	Cost to replace product.
WarrantyContent	NATSPEC BIM Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	Description of what is included in warranty.
WarrantyEndDate	NATSPEC BIM Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	Format: YYYY-MM-DD.
WarrantyIdentifier	Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	Identifier assigned to warranty.

WarrantyPeriod	Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	
WarrantyStartDate	NATSPEC BIM Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	Format: YYYY-MM-DD.
Geometric data		
CrossSectionArea	NATSPEC BIM	
GrossFootprintArea	Qto_WallBaseQuantities (IFC4) IfcWall (IFC2x3)	
GrossSideArea	Qto_WallBaseQuantities (IFC4) IfcWall (IFC2x3)	
GrossSideAreaLeft	IfcWall (IFC2x3)	
GrossSideAreaRight	IfcWall (IFC2x3)	
GrossVolume	NATSPEC BIM IfcWall (IFC2x3)	
Height	NATSPEC BIM Qto_WallBaseQuantities (IFC4)	
Length	NATSPEC BIM Qto_WallBaseQuantities (IFC4)	
NetFootprintArea	Qto_WallBaseQuantities (IFC4) IfcWall (IFC2x3)	Takes all openings or recesses into account.
NetSideArea	Qto_WallBaseQuantities (IFC4) IfcWall (IFC2x3)	Takes all openings or recesses into account.
NetSideAreaLeft	IfcWall (IFC2x3)	
NetSideAreaRight	IfcWall (IFC2x3)	
NetVolume	Qto_WallBaseQuantities (IFC4) IfcWall (IFC2x3)	Takes all openings or recesses into account.

NominalHeight	IfcWall (IFC2x3)	Typically the vertical characteristic dimension of the object.
NominalLength	IfcWall (IFC2x3)	Typically the primary or larger of the two perpendicular horizontal dimensions of the object.
NominalWidth	IfcWall (IFC2x3)	Typically the secondary or smaller of the two perpendicular horizontal dimensions of the object.
Width	NATSPEC BIMQto_WallBaseQuantities (IFC4)	
Manufacturer data		
Accessories	NATSPEC BIM	Details of available accessories.
ArticleNumber	Pset_ManufacturerTypeInformation (IFC4) Pset_ManufacturerTypeInformation (IFC2x3)	Reference applied to product, according to scheme for article number definition defined by manufacturer. Often used as purchasing number.
AssemblyPlace	NATSPEC BIM Pset_ManufacturerTypeInformation (IFC4)	Defines where assembly is to take place. Complete value with: SITE, FACTORY or NOTDEFINED (IfcAssemblyPlaceEnum)
Availability	NATSPEC BIM	
BarCode	Pset_ManufacturerOccurrence (IFC4) Pset_ManufacturerOccurrence (IFC2x3)	Bar code given to occurrence of the product.
BatchReference	Pset_ManufacturerOccurrence (IFC4) Pset_ManufacturerOccurrence (IFC2x3)	Identity of the batch from which the occurrence of the product is taken.
Defects	NATSPEC BIM	To record any defects found.
GlobalTradeItemNumber	Pset_ManufacturerTypeInformation (IFC4)	GTIN is an identifier for trade items developed by GS1 (www.gs1.org).
Manufacturer	NATSPEC BIM Pset_ManufacturerTypeInformation (IFC4) NATSPEC Spec	Name of the manufacturer (or assembler).

	Pset_ManufacturerTypeInformation (IFC2x3)	
ManufacturerURL	NATSPEC BIM	URL hyperlink to the manufacturer's website.
ModelLabel	Pset_ManufacturerTypeInformation (IFC4) NATSPEC BIM	The descriptive model name of the product model (or product line) as assigned by the manufacturer of the manufactured item.
ModelLabel	Pset_ManufacturerTypeInformation (IFC2x3)	The model number and/or unit designator assigned by the manufacturer of the manufactured item.
ModelReference	Pset_ManufacturerTypeInformation (IFC4) NATSPEC BIM NATSPEC Spec	The model number or designator of the product model (or product line) as assigned by the manufacturer of the manufactured item.
ModelReference	Pset_ManufacturerTypeInformation (IFC2x3)	The name of the manufactured item as used by the manufacturer.
OrderNumber	NATSPEC BIM	
PointOfContact	Pset_Warranty (IFC4) Pset_Warranty (IFC2x3)	Organization that should be contacted for action under the terms of the warranty.
ProductInformation	NATSPEC BIM	A valid URL hyperlink to further product information, such as technical documentation, installation guides, etc.
ProductType	NATSPEC BIM	
ProductionYear	Pset_ManufacturerTypeInformation (IFC4) NATSPEC BIM Pset_ManufacturerTypeInformation (IFC2x3)	
SerialNumber	Pset_ManufacturerOccurrence (IFC4) NATSPEC BIM Pset_ManufacturerOccurrence (IFC2x3)	Serial number assigned to an occurrence of a product.
Performance data		
AcousticRating	NATSPEC BIM Pset_WallCommon (IFC4) Pset_WallCommon (IFC2x3)	Acoustic rating for the object. Indicates the sound transmission resistance of the object by an index ratio.

ConcreteCompressiveStrength28Day	BIM Forum	
CondensationResistance	BIM Forum	
Deflection	NATSPEC BIM	
ImpactResistanceHail	BIM Forum	
RValue	BIM ForumNATSPEC BIM	
RadiationResistance	NATSPEC BIM	
ThermalTransmittance	NATSPEC BIMPSet_WallCommon (IFC4)PSet_WallCommon (IFC2x3)	Thermal transmittance coefficient (U-Value).
UVResistance	BIM Forum	
WaterPenetrationResistance	BIM Forum	
WindLoadCapacity	NATSPEC BIM	
WindLoadCapacityDrag	BIM Forum	
WindLoadCapacityPressure	BIM Forum	
Scheduling data		
DeliverBy	NATSPEC BIM	
FabricationTime	NATSPEC BIM	
InstallationSequence	NATSPEC BIM	
InstallationTime	NATSPEC BIM	
LeadTime	NATSPEC BIM	
Spatial and location data		

FloorID	NATSPEC BIM	
GISTag	NATSPEC BIM	
GPSTag	NATSPEC BIM	
SpaceID	NATSPEC BIM	
Specification data		
Combustible	PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Is object made from combustible material. Complete value with: TRUE or FALSE (IfcBoolean)
Compartmentation	PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Is object designed to serve as fire compartmentation. Complete value with: TRUE or FALSE (IfcBoolean)
ConcreteSurfaceFinishClass	NATSPEC Spec	
ExtendToStructure	PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Indicates whether the object extends to structure above. Complete value with: TRUE or FALSE (IfcBoolean)
Finish	NATSPEC BIM	Specification of surface finish.
IsExternal	PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Complete value with: TRUE or FALSE (IfcBoolean)
LoadBearing	PSet_WallCommon (IFC4) PSet_WallCommon (IFC2x3)	Indicates if object is intended to carry loads. Complete value with: TRUE or FALSE (IfcBoolean)
Material	NATSPEC BIM	
MaterialInsulation	BIM Forum	
MaterialSkin	BIM Forum	
MaterialSubstrate	BIM Forum	
ShearReinforcement	BIM Forum	
SpecificationCode	NATSPEC BIM	

SpecificationSystem	NATSPEC BIM	
SpecificationTitle	NATSPEC BIM	
WallType	BIM Forum	
Sustainability data		
CarbonFootprint	NATSPEC BIM	
ItemIsNew	NATSPEC BIM	
ItemIsPartiallyRecycled	NATSPEC BIM	
ItemIsRecycled	NATSPEC BIM	
PostConsumerRecycledContent	NATSPEC BIM	
PostIndustrialRecycledContent	NATSPEC BIM	
PreConsumerRecycledContent	NATSPEC BIM	
RecycledContent	NATSPEC BIM	